

#### **HEAD TYPES**



#### COUNTERSUNK (CSK)

Designed to give a flush finish.



#### **FULL PAN / ROUND HEAD**

Head with a flat underside. Designed for application fixing against metal surfaces.



#### **HEXAGON WASHER HEAD**

A curved surface under the head to prevent

SOCKET BUTTON HEAD

Positive drive Hex Head with an integral washer to increase clamping effectiveness.



#### PHILLIPS RECESS (PH)

POZI / CROSS RECESS (PZ)

A very commonly used drive and standard recess

Standard recess for window screws.

DRIVE / RECESS STYLE

for chipboard screws.



#### SHALLOW PAN

into PVC.

A special head designed for use with friction stays/window hinges to assist with clamping and clearance. This shallow pan head has a locating collar under the head to aid a positive fit with the hardware.

COUNTERSUNK (CSK) WITH RIBS

Designed to give a flush finish with added ribs

under head to assist with countersinking directly



#### FLANGE HEAD SHALLOW PAN

This product has all the features of the above shallow pan with the added benefit of the flange to increase the clamping area.





# SOCKET CAP HEAD

**BUGLE HEAD** 

damage to the material.

to aid clamping.

A flat underside to aid clamping, requires hex key to loosen or tighten.

Designed for a raised finish with a flat underside



#### SQ1/PH2 COMBI DRIVE

Available on a range of non magnetic stainless steel window screws to aid with a positive stick fit.



#### **SQUARE RECESS / DRIVE**

Square drive recess, not to be confused with combi drive.



#### PIN – TORX DRIVE

For security screws

#### THREAD TYPES



# SELF-TAPPING THREAD

applications where a large clamping area is

A common thread design mainly for use in steel or aluminum applications found mainly on selftapping screws, also referred to as self-tappers.



#### TWIN THREAD

Also known as twin lead threads. They are designed to give a fast insertion time in soft material.



#### COARSE THREAD

A standard thread found on our self-drilling screws.



#### FINE THREAD

Also known as metric thread. Only found on self-drilling screws and for use with thicker steel reinforcing.



#### SERRATED THREAD

Reduces the torque required to install the fastener as well as assisting with the speed of insertion.



#### HI-LO THREAD

Hi-Lo threads are found on UKF's 3500 WindowMASTER screw as an alternative to single thread.

#### **POINT STYLES**



#### AB TYPE

For use in pre-drilled sheet material applications, standard on self-tapping screws, also referred to as self-tappers.



## **NEEDLE / GIMLET POINT**

Designed for piercing timber, MDF, PVC and light gauge metal up to 0.6mm without pre-drilling. May also be referred to as sharp point.



#### B TYPE

For use in pre-drilled shallow holes.



#### **CUT 17 TYPE**


Also known as slash point, they are used for fixing timber without the need to pre-drill. The cutting edge helps reduces splitting of the timber.



### SELF-DRILL TIP

For drilling into metals without the need for pre-drilling.






PLEASE REQUEST
OUR CONSUMABLES
AND HARDWARE
CATALOGUE TO
REVIEW OUR
FULL RANGE

# PLEASE REQUEST OUR Aluminium MASTER CATALOGUE

QUALITY FASTENERS FOR ALUMINIUM WINDOWS & DOORS



PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS & BOX INFORMATION										
		(		BOX QTY	16mm	19mm	25mm	30mm	38mm	45mm	55mm			
	3504	4.3	PH2	INNER:	1000	1000	1000	1000	1000	1000	1000			
				OUTER:	10000	10000	4000	4000	4000	4000	2000			
			SQ1/	BOX QTY	16mm	19mm	25mm	30mm	38mm	45mm	55mm			
	3514	4.3	PH2 Combi	INNER:	1000	1000	1000	1000	1000	500	500			
			Drive	OUTER:	10000	10000	8000	4000	4000	4000	2000			
				BOX QTY	19mm	25mm	38mm							
	3503	4.8	PH2	INNER:	1000	1000	1000							
REPAIR SCREW				OUTER:	8000	4000	4000							
USTENITIC, SHALLOW PAN, GIMLET POINT, PVC	ONLY UN	I-REINFO	ORCED											
PRODUCT	UKF Code	THREAD DIA ( <b>mm</b> )	DRIVE Type	LENGTHS &	BOX INFORM	ATION								
				BOX QTY	16mm	19mm	25mm	31mm						
	3574	4.3	PH2	INNER:	1000	1000	1000	1000						
SHALLOW PAN HEAD				OUTER:	10000	8000	4000	4000						
-			SQ1/	BOX QTY	16mm	19mm	25mm	31mm						
	3584	4.3	PH2 Combi	INNER:	1000	1000	1000	1000						
SHALLOW PAN WITH SERRATIONS UNDER HEAD			Drive	OUTER:	8000	8000	4000	4000						
4				BOX QTY	16mm	20mm								
	3573	4.8	PH2	INNER:	1000	1000								
SHALLOW PAN WITH SERRATIONS UNDER HEAD				OUTER:	8000	12000								
4				BOX QTY	13mm	16mm	19mm	25mm	31mm					
	3575	4.8	PH2	INNER:	1000	1000	1000	1000	1000					
FLANGE HEAD SHALLOW PAN				OUTER:	10000	10000	4000	4000	4000					
4			SQ1/	BOX QTY	25mm									
	3585	4.8	PH2 Combi	INNER:	1000									
SHALLOW PAN WITH SERRATIONS UNDER HEAD			Drive	OUTER:	4000									
USTENITIC ONE PIECE SELF DRILLING SCREWS,	ONLY RI	ECOMME	NDED	FOR ALUM	IINIUM									
RODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS &	BOX INFORM	ATION								
				BOX QTY	16mm	19mm	25mm	32mm	38mm	45mm	50mm			
FFFFFFFFFFFF	3400	4.2	PZ2	INNER:	1000	1000	1000	1000	1000	1000	1000			
				OUTER:										
4				BOX QTY	16mm	23mm								
7-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	3000	4.8	PH2	INNER:	1000	1000								

SHALLOW PAN HEAD

OUTER:

8000

4000

AUSTENITIC BI-METAL											
PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS &	BOX INFORMA	TION					
				BOX QTY	16mm	19mm	25mm	29.5mm	32mm	38mm	
	R 4500	4.5	PH2	INNER:	1000	1000	1000	1000	1000	1000	
RIBBED COUNTERSUNK				OUTER:	12000	12000	6000	6000	6000	6000	
			SQ1/	BOX QTY	16mm	19mm	25mm	29.5mm	32mm	38mm	45mm
	QS 4500	4.5	PH2 Combi	INNER:	1000	1000	1000	1000	1000	1000	500
RIBBED COUNTERSUNK			Drive	OUTER:	12000	12000	6000	6000	6000	6000	3000
4.				BOX QTY	16mm	19mm	25mm	29.5mm			
	R 4300	4.5	PH2	INNER:	1000	1000	1000	1000			
SHALLOW PAN HEAD WITH SERRATIONS UNDER HEAD				OUTER:	12000	12000	6000	6000			
4.			SQ1/	BOX QTY	16mm	19mm	25mm	29.5mm			
	QS 4300	4.5	PH2 Combi	INNER:	1000	1000	1000	1000			
SHALLOW PAN HEAD WITH SERRATIONS UNDER HEAD			Drive	OUTER:	12000	12000	12000	6000			
MRX MODIFIED MARTENSITIC											
PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS &	BOX INFORMA	TION					
				BOX QTY	13mm	16mm	19mm	25mm	32mm	38mm	
	6000	3.9	PH2	INNER:	1000	1000	1000	1000	1000	1000	
***************************************				OUTER:	12000	12000	12000	8000	7000	7000	
				BOX QTY	16mm						
THEFT	6200	3.9	PH2	INNER:	1000						
RIBBED COUNTERSUNK				OUTER:	12000						
4				BOX QTY	13mm	16mm	19mm	25mm	28mm		
	5300	4.2	PH2	INNER:	1000	1000	1000	1000	1000		
SHALLOW PAN HEAD				OUTER:	12000	12000	10000	10000	6000		
				BOX QTY	16mm	25mm					
	5000	4.8	PH2	INNER:	1000	1000					
SHALLOW FLANGE PAN HEAD				OUTER:	10000	5000					
410 MARTENSITIC, DACROTISED SILVER 1000											
PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS &	BOX INFORMA	TION					
				BOX QTY	16mm	19mm	25mm	32mm	38mm	45mm NEW SIZE	
	4100	3.9	PH2	INNER:	1000	1000	1000	1000	1000	500	
-				OUTER:	12000	12000	4000	4000	4000	2000	
				BOX QTY	45mm						
	4200	4.8	PH2	INNER:	500						
REDUCED HEAD DIAMETER				OUTER:	2000						
4				BOX QTY	16mm	19mm	25mm	28mm			
	4000	4.3	PH2	INNER:	1000	1000	1000	1000			
SHALLOW PAN HEAD				OUTER:	10000	8000	4000	4000			

AS OUR SCREWS ARE DESIGNED TO SUIT OUR DRIVER BITS, WE STRONGLY RECOMMEND THAT TO ENSURE THE BEST FIT, THESE ARE ALSO PURCHASED FROM UKF

COUNTERSUNK GIMLET POINT (PVC ONLY UN	-IVLIIVI													
PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS 8	BOX INFOR	RMATION								
				BOX QTY	16mm	19mm	22mm	25mm	32mm	38mm	45mm	55mm	65m	m
C'EE'EE'EE'EE'EE'EE'EE	3500	4.3	PH2	INNER:	1000	1000	1000	1000	1000	1000	500	500	500	
HI-LO THREAD				OUTER:	12000	12000	12000	12000	6000	6000	3000	3000	3000	
				BOX QTY	6mm 19	mm 22m	m 25mn	n 28mm	30mm	32mm	35mm	38mm	40mm	45mr
	3501	4.3	PH2	INNER:	1000 10	00 1000	1000	1000	1000	1000	1000	1000	500	500
SINGLE THREAD				OUTER:	2000 12	000 1200	0 12000	6000	6000	6000	6000	6000	3000	3000
				BOX QTY	25mm	38mm								
- trititititititi	3515	4.8	PH2	INNER:	1000	1000								
HI-LO THREAD REPAIR SCREW				OUTER:	12000	6000								
N				BOX QTY	25mm	38mm	70mm NEW SIZE							
CEEEEEEEEE	3516	4.8	PH2	INNER:	1000	1000	200							
SINGLE THREAD REPAIR SCREW				OUTER:	12000	6000	1200							
	25/2	, ,	DUA	BOX QTY	45mm								-	
HEAD DIAMETER 9.5MM	3542	4.8	PH2	INNER:	500 3000									
				OUILIN.	3000									
COUNTERSUNK SELF DRILLING (REINFORCE) PRODUCT	UKF	THREAD DIA	DRIVE	LENGTHS 8	BOX INFOR	RMATION								
			DRIVE Type	LENGTHS &	BOX INFOR	MATION 16mm	19mm							
	UKF	DIA					19mm 1000							
	UKF CODE	DIA (mm)	TYPE	BOX QTY	13mm	16mm								
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING	UKF CODE	DIA (mm)	TYPE	BOX QTY INNER:	13mm 1000	16mm 1000	1000	25mm	28mm	32mm	38mm			
PRODUCT	UKF CODE	DIA (mm)	TYPE	BOX QTY INNER: OUTER:	13mm 1000 12000	16mm 1000 12000	1000 12000	25mm 1000	28mm 1000	32mm 1000	38mm 1000			
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING	UKF CODE	3.9	PH2	BOX OTY INNER: OUTER: BOX OTY	13mm 1000 12000 16mm	16mm 1000 12000 19mm	1000 12000 22mm							
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD	UKF CODE	3.9	PH2	BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000	16mm 1000 12000 19mm 1000	1000 12000 22mm 1000	1000	1000	1000	1000			
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD	UKF CODE	3.9	PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER:	13mm 1000 12000 16mm 1000 12000	16mm 1000 12000 19mm 1000	1000 12000 22mm 1000 12000	1000 12000	1000	1000	1000			
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD	UKF CODE 3530	3.9 4.0	PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY	13mm 1000 12000 16mm 1000 12000	16mm 1000 12000 19mm 1000 12000	1000 12000 22mm 1000 12000 16mm	1000 12000 19mm	1000	1000	1000			
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD	UKF CODE 3530	3.9 4.0	PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000 12000 11mm	16mm 1000 12000 19mm 1000 12000 14mm	1000 12000 22mm 1000 12000 16mm 1000	1000 12000 19mm 1000	1000	1000	1000	38mm	45m	m 5
PRODUCT  RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD	UKF CODE 3530	3.9 4.0	PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000	1000 12000 19mm 1000 12000 22mm	1000 12000 25mm	1000 6000 28mm 1000	1000 6000 32mm 1000	1000	500	5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD	UKF CODE  3530  3555  3560	3.9 4.0	PH2 PH2 PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: OUTER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000	1000 12000 22mm 1000 12000 16mm 1000 12000	1000 12000 19mm 1000 12000 22mm	1000 12000 25mm	1000 6000 28mm	1000 6000 32mm			5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD  COUNTERSUNK SELF DRILLING REINFORCING SCREW	3530 3555 3560 3525	3.9 4.0 4.0	PH2 PH2 PH2 PH2	BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000 45mm	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000	1000 12000 19mm 1000 12000 22mm	1000 12000 25mm	1000 6000 28mm 1000	1000 6000 32mm 1000	1000	500	5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD  COUNTERSUNK SELF DRILLING REINFORCING SCREW	UKF CODE  3530  3555  3560	3.9 4.0	PH2 PH2 PH2	BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000 45mm 500	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000	1000 12000 19mm 1000 12000 22mm	1000 12000 25mm	1000 6000 28mm 1000	1000 6000 32mm 1000	1000	500	5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD  COUNTERSUNK SELF DRILLING REINFORCING SCREW	3530 3555 3560 3525	3.9 4.0 4.0	PH2 PH2 PH2 PH2	BOX OTY INNER: OUTER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000 45mm 500 3000	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm 1000 12000	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000 12000	1000 12000 19mm 1000 12000 22mm 1000 12000	1000 12000 25mm 1000 12000	28mm 1000 6000	32mm 1000 6000	1000	500	5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD  COUNTERSUNK SELF DRILLING REINFORCING SCREW  HEAD DIAMETER BMM	3530 3535 3555 3560 3525	3.9 4.0 4.2	PH2 PH2 PH2 PH2	BOX OTY INNER: OUTER: BOX OTY INNER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000 45mm 500	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000	1000 12000 19mm 1000 12000 22mm	1000 12000 25mm	1000 6000 28mm 1000	1000 6000 32mm 1000	1000	500	5
RIBBED COUNTERSUNK / REINFORCING RETENTION / PINNING  FINE THREAD  RIBBED COUNTERSUNK / REINFORCING RETENTION PINNING / FINE THREAD  COUNTERSUNK SELF DRILLING REINFORCING SCREW	3530 3555 3560 3525	3.9 4.0 4.0	PH2 PH2 PH2 PH2	BOX OTY INNER: OUTER:	13mm 1000 12000 16mm 1000 12000 11mm 1000 12000 13mm 1000 12000 45mm 500 3000	16mm 1000 12000 19mm 1000 12000 14mm 1000 12000 16mm 1000 12000	1000 12000 22mm 1000 12000 16mm 1000 12000 19mm 1000 12000	1000 12000 19mm 1000 12000 22mm 1000 12000	1000 12000 25mm 1000 12000	28mm 1000 6000	32mm 1000 6000	1000	500	5

REDUCED HEAD DIAMETER / ENHANCED PULL OUT RESISTANCE

OUTER:

6000

3000

3000

3000

3000

SHALLOW PAN / FLANGE HEAD SHALLOW PAN HEAD GIMLET POINT (PVC ONLY UN-REINFORCED)														
PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE TYPE	LENGTHS &	BOX INFOR	MATION								
1				BOX QTY	16mm	19mm	25mm	31mm						
	3576	4.8	PH2	INNER:	1000	1000	1000	1000						
FLANGE HEAD SHALLOW PAN				OUTER:	12000	12000	6000	6000						
4				BOX QTY	13mm	16mm	19mm	25mm	31mm					
	3577	4.3	PH2	INNER:	1000	1000	1000	1000	1000					
SHALLOW PAN HEAD				OUTER:	12000	12000	12000	6000	6000					
				BOX QTY	19mm	25mm								
OURSE SHALL SHE BANK MEAN PLANTED	3581	4.8	PH2	INNER:	1000	1000								
SUPER SHALLOW PAN 9MM HEAD DIAMETER				OUTER:	12000	6000								
4			PH2	BOX QTY	25mm									
4	3581	4.8		INNER:	1000									
SUPER SHALLOW PAN 8MM HEAD DIAMETER				OUTER:	6000									
4	3583	4.8	T20	BOX QTY	25mm									
				INNER:	1000									
SUPER SHALLOW PAN 9MM HEAD DIAMETER SECURITY SCREW				OUTER:	6000									
SHALLOW PAN HEAD SELF DRILLING (REINF	ORCED)													
PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS &	BOX INFOR	MATION								
				BOX QTY	16mm	19mm								
	3520	3.9	PH2	INNER:	1000	1000								
MEDIUM HEIGHT PAN HEAD				OUTER:	12000	12000								
4				BOX QTY	16mm	19mm	25mm							
TELEFECTE CONTRACTOR OF THE PROPERTY OF THE PR	3578	4.8	PH2	INNER:	1000	1000	1000							
FLANGE HEAD SHALLOW PAN				OUTER:	12000	12000	6000							
A				BOX QTY	13mm	16mm	19mm	25mm	28mm					
	3579	4.3	PH2	INNER:	1000	1000	1000	1000	1000					
SHALLOW PAN HEAD				OUTER:	12000	12000	12000	6000	6000					
<b></b>				BOX QTY	16mm	28mm								
	3580	M4	PH2	INNER:	1000	1000								
SHALLOW PAN HEAD / FINE THREAD				OUTER:	12000	6000								
				BOX QTY	19mm	25mm								
4	3582	4.8	PH2	INNER:	1000	1000								
SUPER SHALLOW PAN 9MM HEAD DIAMETER				OUTER:	12000	6000								

	CARBON STEEL RANGE														
	3590 – BAYPOLE / MECHANICAL JOINTING SC	REW													
ı	PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS & I	BOX INFORI	MATION								
Ī	d				BOX QTY	50mm	60mm	70mm	80mm	90mm	100mm	120mm NEW SIZE			
		3590	4.8	PH2	INNER:	200	200	200	200	100	100	100			
	'				OUTER:	2400	1600	1600	1600	800	800	800			
					BOX QTY	60mm	70mm	80mm							
ì		3591	5.5	PH2	INNER:	200	200	200							
	1				OUTER:	1600	1600	1600							
	3551 - MECHANICAL JOINTING SCREW			,											
	PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS & I	BOX INFORI	MATION								
ľ					BOX QTY	50mm	55mm	65mm	75mm						
	<del></del>	3551	4.2	PH2	INNER:	500	500	200	200						
					OUTER:	3000	3000	2400	2400						
	70 – JOINING FRAME TO TRANSOM / MULLION														
	PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS & I	BOX INFORI	MATION								
ľ	A				BOX QTY	55mm	65mm	80mm	95mm						
	www.	3570	4.8	PH2	INNER:	200	200	100	100						
					OUTER:	2400	2400	1200	1200						
	RIP RAIL – WEATHER BAR SCREWS – NIPPLE HEAD														
	PRODUCT	UKF CODE	THREAD DIA ( <b>mm</b> )	DRIVE Type	LENGTHS & I	BOX INFORI	MATION								
	dh.				BOX QTY	13mm									
	1111111	3595	4.0	PH2	INNER:	1000									
L	HEAD DIAMETER 10.4MM / SELF DRILLING				OUTER:	6000									
					BOX QTY										
		3594	4.0	PH2	INNER:	1000									
ŀ	HEAD DIAMETER 10MM				OUTER: BOX QTY	6000									
		3594	4.0	PH2	INNER:	12mm 1000									
	HEAD DIAMETER 9MM	0074	4.0	1112	OUTER:	6000									
	3588 - GLAZING CASSETTE SCREW				0012111										
	PRODUCT	UKF CODE	THREAD DIA (mm)	DRIVE Type	LENGTHS & I	BOX INFORI	MATION								
ľ	_				BOX QTY	38mm									
		3588	4.3	PH2	INNER:	1000									
L					OUTER:	3000									
	HANDLE SCREWS - AVAILABLE IN CARBON S	TEEEL	AND ST	AINLES	S STEEL										
	PRODUCT	UKF Code	THREAD DIA (mm)	DRIVE Type	LENGTHS & I	BOX INFOR	MATION								
ſ					BOX QTY	10mm	12mm	14mm	16mm	20mm	25mm	30mm	35mm	40mm	50mm
	CARBON STEEL	M5	M5	PH2	INNER:	1000	1000	1000	1000	1000	1000	1000	1000	1000	500
					BOX QTY	12mm	14mm	16mm	20mm	25mm	30mm	35mm	40mm	50mm	
	STAINLESS STEEL	M5	M5	PZ2	INNER:	1000	1000	1000	1000	1000	1000	1000	1000	500	

INSTALLATION FIXINGS																
DIRECT FIX CONCRETE SCREWS																
PRODUCT	UKF Code	THREAD DIA (MM)	DRIVE Type	LENGTHS	& BOX INFO	RMATION										
B				BOX QTY	52mm	62mm	72mm	82mm	92mm	102mm	112mm	122mm	132mm	142mm	152mm	182mn
Sammummumm	9000	7.5	T30	INNER:	1000	1000	1000	1000	100 800	100 800	100 600	100 600	100 600	100 600	100	100 400
				BOX QTY	57mm	70mm	82mm	1000 100mm	800	000	000	000	000	000	000	400
	9200	4.5	PH2	INNER:	100	100	100	100								
9200 SALT SPRAY TESTED TO 500 HOURS				OUTER:	2400	2000	2000	1200								
HEAVY DUTY SELF DRILLING SCRE	W															
PRODUCT		UKF COD		TVDF	LENGTHS	& BOX IN	IFORMATI	DN								
					BOX QTY		m									
		354	3 5.	5 PH3		200										
NYLON FRAME ANCHORS				OUTER:	240											
PRODUCT		UKF		READ DRI'	/E LENGTU	C o DOV I	NEODMAT	ION								
	TVDE	COD	E DIA ( <b>m</b>	. TVD		S & BOX I	NFUKMAI	IUN								
NYLON FRAME FIXING – SCREW IN	ITTE				BOX QTY	' 10r	)mm									
With the state of	700	0 8.1	O PZ		100											
1)11)				OUTER:												
NYLON FRAME FIXING – HAMMER IN 1	YPE															
		F40			BOX QT			0mm								
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		710	0 8.	0 PZ:	2 INNER: OUTER:		J 1	00								
NYLON FRAME FIXING – HAMMER IN 1	YPE				OOTER											
					BOX QT	Y 50r	nm									
		710	0 5.	O PZ												
					OUTER:											
NYLON FRAME ANCHOR (2 PIECE)																
	-	720	0 8.	0 PZ	BOX QT 3 INNER:			120mm 100	140mm 100							
<u> </u>		720	0.	12	OUTER:			100	100							
PLASTIC HEADED NAIL & PIN RANG	GE (BL	ACK / WI	HITE / T	AN / BR	DWN / ST	AINLES	S)									
PRODUCT		UKF CODE			THRE DIA (mn		LENGTH	S & BOX I	NFORMATIO	DN						
	CAPPIN		IG PIN		2.0	BOX QTY		30mm 250								
	PLASTIC HE					2.0	BOX QTY		25mm 250	30mm 250	40mm 250					
1	PLASTIC HEA						BOX QTY INNER:			50mm	65mm					

= CODE = 3590/80Z

9

#### **GRIPTIGHT PLUS® MULTI PURPOSE SCREW** UKF CODE PRODUCT DESCRIPTION LENGTH & FINISHES AVAILABLE HARDENED STEEL 3.0MM TO 6.0MM DIA. & IN **GRIPTIGHT PLUS** STEEL **POZI** CSK OR ROUND HEAD LENGTHS FROM 12MM TO 150MM MULTI PURPOSE SCREW

#### **ALSO AVAILABLE IN A2 STAINLESS STEEL**

GRIPTIGHT PLUS SCREWS ARE MANUFACTURED FROM HIGH QUALITY CARBON STEEL, WHICH IS THEN HEAT TREATED TO GIVE EXCEPTIONAL TOUGHNESS FROM HEAD TO POINT. PROTECTIVE FINISH IN ZINC & ZINC/YELLOW WAXED TO AID INSTALLATION SPEED.

	DIAM		LEN	IGTH	HEAD :		PACK	INFO		IETER		LEN		HEAD	STYLE	INFO	
ММ	DRIVE TYPE	GAUGE	MM	INCH	CSK	RND	INNER	OUTER	ММ	DRIVE TYPE	GAUGE	MM	INCH	CSK	RND	INNER	OUTER
			12	1/2"	•	•	1000	60000				25	1"	•		500	6000
			15	5/8"	•	•	1000	40000				30	1.1/4"	•	•	500	6000
3	PZ1	NO.4	16	5/8"	•		1000	40000				35	1.3/8"	•		500	6000
			20	3/4"	•		1000	34000	-			40	1.1/2"	•		500	6000
			30	1.1/4"	•		1000	22000	4.5	PZ2	NO.10	45	1.3/4"	•		500	5000
			12	1/2"	•		500	32000				50	2"	•		500	5000
			15	5/8"	•	•	500	30000				60	2.3/8"	•		200	2400
			16	5/8"	•		500	30000	_			70	2.3/4"	•		200	2400
			17	5/8"	•		500	30000				80	3.1/8"	•		200	2000
			20	3/4"	•		500	30000				25	1"	•		500	6000
3.5	D72	NO 4				•	500	17000				30	1.1/4"	•	•	500	6000
3.3								35	1.3/8"	•	•	500	6000				
			30	1.1/4"	•	•	500	11000				40	1.1/2"	•	•	500	5000
			35	1.3/8"	•	•	500	11000				45	1.3/4"	•		500	3000
			40	1.1/2"	•		500	6000	5	PZ2	NO.12	50	2"	•		500	3000
			45	1.3/4"	•		500	6000				60	2.3/8"	•		200	3000
			50	2"	•		500	6000				70	2.3/4"	•		200	2000
			15	5/8"	•	•	500	20000				80	3.1/8"	•		200	2000
			20	3/4"	•		500	20000				90	3.1/2"	•		200	2000
			25	1"	•	•	500	17000				100	4"	•		200	2000
			28	1.1/8"	•		500	11000				120 40	4.3/4" 1.1/2"	•		200	1000 2000
			30	1.1/4"	•		500	11000				50	2"	•		200	3000
,	D70	NO O	35	1.3/8"	•		500	11000				60	2.3/8"	•		200	2000
4	PZ2	NO.8	40	1.1/2"	•	•	500	6000	6			80	3.1/8"	•		200	2000
			45	1.3/4"	•		500	6000		PZ3	NO.14	90	3.1/2"	•		200	2000
			50	2"	•	•	500	5000				100	4"	•	•	200	2000
			55	2.1/4"	•		500	3000				120	4.3/4"	•		200	600
			60	2.3/8"	•		500	3000				130	5.1/4"	•		200	600
			70	2.3/4"	•		500	2500				150	6"	•		200	600
				THREAD	I FNGTH.							FIII	IY THREA	DED OPTI	NS.		

THREAD LENGTH: FULLY THREADED OPTIONS:

AS STANDARD ALL DIAMETERS UP TO AND INCLUDING 50MM LONG ARE FULL THREADED. ALL OTHERS ARE PART THREADED.

FULL THREADED LONGER LENGTH OPTIONS ALSO AVAILABLE FROM STOCK.





